

Identify stairwells or ramps with this custom made floor identification sign.

MEETS IBC/IFC REGULATION



Identification of the stair or ramp

Floor level

Braille floor identifier

Terminus of the top & bottom of the exit enclosure

Availability of roof access from the enclosure (for the fire dept.)

Story of and direction to the exit discharge

IFC 1022.8 states: A sign shall be provided at each floor landing in exit enclosures connecting more than three stories designating the floor level, the terminus of the top and bottom of the exit enclosure and the identification of the stair or ramp. The signage shall also state the story of, and the direction to, the exit discharge and the availability of roof access from the enclosure for the fire department. The sign shall be located 5 feet above the floor landing in a position that is readily visible when the doors are in the open and closed position. Floor level identification signs in tactile characters complying with ICC A117.1 shall be located at each floor level landing adjacent to the door leading from the enclosure into the corridor to identify the floor level.

Related Products

- Glo Brite[®] Eco Exit[™] Signs
- Glo Brite[®] Machine Labels
- Glo Brite[®] 7550 Exit Signs
- Glo Brite[®] ADA Braille Signs
- Glo Brite[®] Walk on Floor Signs

Specifications

- 18" x 12" Sign
- Made from high quality rigid plastic
- Tactile raised letters
- Braille beads

Features

- Custom made for each location
- Listed UL 1994; or ASTM E 2072, except that the charging source shall be 1 foot-candle (11 lux) of fluorescent illumination for 60 minutes, and the minimum luminance shall be 30 millicandelas per square meter at 10 minutes and 5 millicandelas or square meter after 90 minutes
- 1022.8 Illumination: Exit enclosures where photoluminescent exit path markings are installed shall be provided with the minimum means of egress illumination required by Section 1006 for at least 60 minutes prior to periods when the building is occupied

View all of our Floor ID Signs at
nationalmarker.com

